

DF2.5

Lightweight and portable

- Easy to control, with forward & neutral gears plus 180° rotation for reverse.
- Easy to transport due to light weight and convenient carry handle.
- Quiet and fuel-efficient operation courtesy of water cooling.

MODEL	DF2.5
SHAFT LENGTH mm	S:381 L:508
STARTING SYSTEM	Manual
WEIGHT (kg)	13.5 / 14.0
ENGINE TYPE	OHV
FUEL DELIVERY SYSTEM	Carburettor
NO. OF CYLINDERS	1
PISTON DISPLACEMENT cm ³	68
BORE x STROKE m/m	48 X 38
MAXIMUM OUTPUT kW	1.8
FULL THROTTLE OPERATING RANGE rpm	5,250-5,750
STEERING	Tiller (Full pivot)
CHOKE	Manual
OIL PAN CAPACITY (litres)	0.3
FUEL TANK CAPACITY (litres)	Integral 1
IGNITION SYSTEM	Suzuki P.E.I.
ALTERNATOR	N/A
ENGINE MOUNTING	Bushing Type
TRIM METHOD	Manual Trim & Tilt
GEAR RATIO	2.15:1
GEAR SHIFT	F-N
EXHAUST	Above Prop
PROPELLOR SELECTION (pitch)	5.38"

THE
ULTIMATE
4-STROKE OUTBOARD