

DF4A

Packed with features

- Easy to transport and store courtesy of a new three-way storage capability which eliminates the worry of fuel or oil leakage.
- Easy to lift and carry with two sturdy handles.
- Easy to start after storage courtesy of a new forced lubrication and gravity-fed fuel system.
- Easy to use with new tilt system.
- Smooth and quiet running thanks to an offset crankshaft.
- Low vibration as a result of a new tiller handle design.

MODEL	DF4A
SHAFT LENGTH mm	S:381 L:508
STARTING SYSTEM	Manual
WEIGHT (kg)	24.0 / 25.0
ENGINE TYPE	OHV
FUEL DELIVERY SYSTEM	Carburettor
NO. OF CYLINDERS	1
PISTON DISPLACEMENT cm ³	138
BORE x STROKE m/m	60.4 X 48
MAXIMUM OUTPUT kW	2.9
FULL THROTTLE OPERATING RANGE rpm	4,000-5,000
STEERING	Tiller
CHOKE	Manual
OIL PAN CAPACITY (litres)	0.7
FUEL TANK CAPACITY (litres)	Integral 1.0
IGNITION SYSTEM	Digital CDI
ALTERNATOR	12V 5A (OP)
ENGINE MOUNTING	Bushing Type
TRIM METHOD	Manual Trim & Tilt
GEAR RATIO	1.92:1
GEAR SHIFT	F-N-R
EXHAUST	Above Prop
PROPELLOR SELECTION (pitch)	6" - 7"

THE
ULTIMATE
4-STROKE OUTBOARD