

DF60A

Compact, lightweight and fuel-efficient

- High tech advanced performance and fuel efficiency from a Double Overhead Cam (DOHC) engine.
- Quicker acceleration, higher top-end speed and increased torque from the largest reduction gear ratio in its class.
- Reliability and easy maintenance at its best with our self adjusting oil bathed timing chain.
- 40hp and 50hp models also available. Please ask a member of the team for details.





Market-leading fuel efficiency

Exclusive theft deterrent

MODEL	DF60A
SHAFT LENGTH mm	S:381 L:508 X:635
STARTING SYSTEM	Electric
WEIGHT (kg)	104.0 (S)
ENGINE TYPE	DOHC
FUEL DELIVERY SYSTEM	Multi Point EFI
NO. OF CYLINDERS	3
PISTON DISPLACEMENT cm ³	941
BORE x STROKE m/m	72.5 X 76.0
MAXIMUM OUTPUT kW	44.1
FULL THROTTLE OPERATING RANGE	5,300-6,300
rpm	
STEERING	Remote
CHOKE	-
OIL PAN CAPACITY (litres)	2.7
IGNITION SYSTEM	Transistorised
ALTERNATOR	12V 19A
ENGINE MOUNTING	Shear Type
TRIM METHOD	Power Trim & Tilt
GEAR RATIO	2.27:1
GEAR SHIFT	F-N-R
EXHAUST	Through Prop
PROPELLOR SELECTION (pitch)	15" - 21"

