

DF150AP

High-end performance and features put the new DF175AP/150AP in a rank above the rest.

- Impressive acceleration and low-end torque courtesy of a high 10.2:1 compression ratio and largest in class displacement.
- Easy, convenient operation and increased security with Suzuki Keyless Start System
- Incredible fuel efficiency from unrivalled Lean Burn Technology.



Exclusive theft deterrent



Market-leading fuel efficiency



Super smooth control



Market-leading versatility

THE
ULTIMATE
4-STROKE OUTBOARD

MODEL	DF150AP
SHAFT LENGTH mm	L:508 X:635
STARTING SYSTEM	Electric
WEIGHT (kg)	L: 234 X:239
ENGINE TYPE	DOHC 16-Valve
FUEL DELIVERY SYSTEM	Multi Point EFI
NO. OF CYLINDERS	In-Line 4
PISTON DISPLACEMENT cm ³	2,867
BORE x STROKE m/m	97 x 97
MAXIMUM OUTPUT kW	110.0
FULL THROTTLE OPERATING RANGE rpm	5,500-6,000
STEERING	Remote
OIL PAN CAPACITY (litres)	8.0
IGNITION SYSTEM	Transistorised
ALTERNATOR	12V 44A
ENGINE MOUNTING	Shear Mount
TRIM METHOD	Power Trim & Tilt
GEAR RATIO	2.50:1
GEAR SHIFT	F-N-R
EXHAUST	Through Prop
PROPELLOR SELECTION (pitch)	17" - 27.5"